



Defoamer

RP-6615

Features and advantages:

- ◆ Molecular defoamer, without APEO;
- ◆ It is very suitable for the system with high bubble suppression requirements, and the effect of eliminating the microbubbles of the paint film is good in airless spraying and air spraying;
- ◆ Excellent bubble suppression and micro-bubble control performance, and has a wetting effect, the film will not appear oil shrinkage;
- ◆ In the low PVC system, the foam suppression force is outstanding, and the paint film will not shrink, and the gloss of the paint film will not be affected.

Product specification:

appearance	Pale yellow opaque liquid
Active matter	100%
viscosity	200 (25°C) ~2000 (5°C) mPa.s
Specific gravity	0.83-0.89g/mL (20°C)
Main component	Mineral oil, modified polyether
ionicity	nonionic

Application field:

Inorganic paint, waterborne wood paint, waterborne industrial paint, waterborne paint, adhesive system can be used.

Usage and addition amount:

Coating can be added in the form of original material;
Add 50% of the mass in the grinding stage and the remaining 50% in the paint mixing stage (before adding the emulsion);

Tianjin Ruike Chemical Co. LTD

Tel:+86 18526852692

Add:Room 116-11, 160 Xiangyuan Road, Jingjin Science and Technology Valley Industrial Park, Wuqing District, Tianjin

tjrkhg@126.com

www.rk-chem.com



When using the product for the first time, add the lowest amount until the best effect is achieved;

Stir well or shake well before use. (The layering that occurs during storage does not affect usage efficiency).

Packing: 25KG/180KG plastic drum;

Storage: The shelf life of the product is 12 months (from the date of production) when it is in an unopened original container and stored at a temperature between -5°C and 40°C .