



High performance wetting agent

RK-8213

Features and advantages:

For water-based formulation, also suitable for solvent-based wetting agent and solvent-free wetting agent (two-component) formulation, good miscibility, excellent spraying wetting agent, high temperature resistance, good recoating property, good adhesion, especially suitable for automotive paint wetting agent, PVC substrate wetting agent, industrial coating wetting agent, architectural coating substrate wetting agent, decorative coating substrate wetting agent.

1. For water-based formulations, also suitable for solvent-based and solvent-free (two-component) formulations
2. Acid and alkali resistance (PH5-10)
3. Excellent anti-shrinkage hole effect
4. Good recoating
5. Additional flow promotion
6. High temperature resistance and good adhesion

Product specification:

appearance	Transparent liquid
Active matter	100%
Chemical composition	Organosiloxane copolymer

Application field:

○Car paint

Recommended addition



Total formula in the form of supply: 0.05-1.0%

○Trade paint

Recommended addition

Total formula in the form of supply: 0.1-1.0%

○Architectural paint

Recommended addition

Total formula in the form of supply: 0.1-1.0%

○Decorative paint

Recommended addition

Total formula in the form of supply: 0.2-1.0%

○Inkjet ink

Recommended addition

Total formula in the form of supply: 0.1-1.0%

Usage: Pre-dilution or directly added to the paint according to the supply form

Packing: 25kg, plastic drum; 200 kilos, iron drum

Storage and precautions: Store unopened in the original packaging and use within 12 months from the date of production.