Defoaming agent

RP-6080

Features and advantages:

It is a highly effective defoaming and defoaming agent for solvent and solvent free coating systems. Effective in production and processing, especially recommended for epoxy resin systems.

Product specifications:

Appearance	Turbid liquid
Composition	Foam breaking polymer and polysiloxane solution
Refractive index	1.448
Solvent	Hydrocarbon mixture
Flash point	95 °C
Density (20℃)	0.81 g/ml

Application:

industrial coatings, architectural coatings, wood and furniture coatings, especially recommended in anti-corrosion coatings.

Recommended dosage:

0.2-0.8% Dosage of auxiliaries (form of supply) based on total formulation.

Usage:

To get the best defoaming effect, defoaming agent should be added to the abrasive.If added at a later stage, shear forces must be applied high enough to ensure good dispersion and thus prevent shrinkage.

Packing:

25kg/ drum.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; For more information, please visit: https://www.rk-chem.com

Storage:

Keep away from sources of fire and light; store in a dark place.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; For more information, please visit: https://www.rk-chem.com